



IAF Air Filters

IAF BIOSAFETY CABINET WITH INTERFACE



The IAF Biosafety Cabinet Touchscreen is an enhanced version of our local. Providing operator, product and environment protection from hazardous aerosols through superior minipleat Hepa Filters, the product combines the best product performance features with IAF.

The cabinet features antimicrobial coated external body structure and reduced overall height for low-ceiling laboratories.

TECHNICAL PARAMETER

- Internal Size (W x D x H) : 1200mm x 630mm x 660mm
- External Size (W x D x H) : 1300mm x 800mm x 2300mm
- Tested Opening : Safety Height 200mm(8")
- Max Opening : 410mm (16.5")
- Inflow Velocity : 0.53, ⁺0.025m/s
- Dowflow Velocity : 0.53, ⁺0.025m/s
- Hepa Filter : Two. 99.999% Efficiency
- Front Window : Acrylic Thk. 6mm
- Noise : NSF 49<
- Caster : Footmaster Caster
- IUV Lamp 21 Watt
- Fluorescent Lamp 36 Watt
- Illumination > 1000Lux
- Consumption 700 Watt
- Display : Push Switch Lamp - Touchscreen
- Air Flow System 0% Air Re-Circulation
100% Air Exhaust
- Material Stainless Steel 304 Mirror
- Work Surface Height 660mm
- Power Supply :
AC 220V + 10%, 50Hz; 110 + 10%, 60Hz